

## URSA FDP 1

MW-EN-13162-T3-MU1-WL(P)-AF5


Lagane izolacione ploče od mineralne staklene vune - vodoodbojne.

Toplotna i zvučna izolacija spoljašnjih zidova u sistemu ventilisanih ili neventilisanih fasada za objekte niže spratnosti.



Tehničke karakteristike	Vrednost	Standard
Toplotna provodljivost $\lambda_D$	0,038 W/mK	EN 13162
Klasa gorivosti	A1	EN 13501-1
Linearni otpor strujanju vazduha	> 5 kPa s/m <sup>2</sup>	
Granična temperatura upotrebe	200°C	

Debljina [mm]	50	80	100	120	140	160	180	200	220	240
Širina [mm]	600	600	600	600	600	600	600	600	600	600
Dužina [mm]	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250
Toplotni otpor $R_D$ [m <sup>2</sup> K/W]	1,30	2,10	2,60	3,15	3,65	4,20	4,70	5,25	5,75	6,30



Proizvod je sertifikovan u skladu sa EN 13162.  
EG sertifikat o usaglašenosti br. : 0672 – CPR – 0319.

**MW** – skraćena oznaka za mineralnu vunu  
**EN 13162** – broj evropskog standarda  
**Ti** – granična odstupanja debljine  
**TRi** – zatezna čvrstoća upravno na ravan ploče  
**WL(P)** – dugotrajno upijanje vlage  
**MUi** – paropropusnost materijala  
**SDi** – nazivna vrednost dinamičke krutosti  
**CPI** – stišljivost  
**AFi** – otpor strujanju vazduha